



R & V Aqualine
1933 Carboor Everton Rd,
Carboor, Victoria, Australia, 3678
Phone 61 (0)3 5729 5556
www.safaritanks.com.au

KTM 2020 EXC 16L Tank

IMPORTANT!

Pre-fitting Instructions for Safari Fuel Tanks

1. These instructions assume that the installer is familiar with removing and installing the OEM fuel tank that comes standard with this motorcycle. These instructions will highlight the unique steps to install the Safari tank. Please read the complete instruction before starting to install the fuel tank.
2. Rinse tank out with a small amount of petrol and then discard the petrol. This needs to be done to remove any plastic trimmings that may be left in the tank after manufacturing.
3. Before attaching the screws and bolts to the brass inserts, ensure that an anti-seize compound – grease will do – is applied to the threads. **Do not use thread retaining compounds.** If there is a risk of the screws and bolts working loose, use lock wire to secure them – mainly for endurance competition events.

Parts listing

- ☐ 1 x Fuel cap and breather
- ☐ 2 x Seat Buttons (installed on the tank)



Installing the tank set

1. Remove the seat and plastic radiator shrouds to allow the fuel tank to be removed.
2. Remove the fuel tank.
3. Remove the EFI fuel pump from the OEM tank.
4. Ensure the Safari fuel tank is clean before starting the installation of the EFI fuel pump into the Safari tank.
5. Install the Safari tank in the reverse steps to removing the OEM tank.
Note: the radiator shrouds are not used with the Safari Tank.
6. After connecting the fuel line to the EFI fuel pump and the throttle body, turn the ignition 'on' (don't start the motor) and check for fuel leaks.